

1U NANO | W314

Unser 1U Nano bietet eine mühelose Installation. Einfach zu montieren und erfrischend vielseitig, verzichtet er auf Schnickschnack um der Funktion willen.


PERFECT FOR



NOISE

38dB

EFFICIENCY



PRODUCT DETAILS

SYSTEM SPECIFICATIONS

| | |
|--------------------------|---|
| CPU: | Intel i3-14100 3.5GHz 4C/8T |
| RAM: | 8GB Crucial DDR5 4800MHz DIMM |
| HDD: | 500GB M.2 NVMe Crucial P3 SSD |
| RAID: | RAID 0, 1, 5, 10 RAID 0, 1, 5 (NVMe/SATA) RAID10 (SATA) |
| DVD: | No DVD drive bay |
| GFX Output: | Intel UHD 730 with HDMI , DisplayPort Output(s) |
| GFX Card: | None |
| LAN: | Intel I226V (2.5Gb/s) & Intel i219V (1Gb/s) |
| WLAN: | Not Quoted - Internal Wi-Fi & BT Option |
| USB Ports Rear: | 1x USB2.0, 4x USB3.2 Gen2, 1x USB-C Gen3 |
| Serial Ports: | Not available |
| Expansion Slot 1: | Not Quoted - Option Available |
| PSU: | 250W 100-240VAC 60-50Hz 80PLUS |
| Lead Time: | 5 Working Days |
| Audio Ports: | 2x 3.5mm Ports (Stereo Out, Mic In) & Optical Digital |
| Warranty: | Standard Only |

CASE INFORMATION

| | |
|--------------------------|--------------------------------------|
| Front USB: | 2x USB3.0 |
| Hot Swap HDD Bay: | Up to 2x 2.5" HDD/SSD Bay |
| PCIe Slots: | Up to 2x PCIe x16 (x8 Lanes) |
| Power Supply: | Single 110-230VAC, 12-48VDC or PoE++ |
| Weight: | 6 KG |
| Size: | 436x211x44.4mm |

MOTHERBOARD IO PORTS



To discuss your requirements or get a bespoke solution for your rack mountable PC needs, please **contact us today**.

+49 (0)6187 290150
sales@g2digital.de