


POCKET | C38L

Unser industrietauglicher Pocket-Mini-PC mit interner Stromversorgung ist in einem wandmontierbaren Gehäuse untergebracht.

PERFECT FOR




ENTRY LEVEL



NOISE

38dB

EFFICIENCY



PRODUCT DETAILS

SYSTEM SPECIFICATIONS

CPU:	Intel i3-8100 3.6GHz 4C/4T*
RAM:	4GB Crucial DDR4 2666MHz DIMM 1.2V
HDD:	120GB 2.5" SATAIII Kingston A400 SSD *
DVD:	No DVD drive bay
GFX Output:	HD630 with VGA, DVI-D, HDMI Output(s)
GFX Card:	None
LAN:	Realtek 8111H
WLAN:	Not Quoted - USB or PCI(e) Card option
USB Ports Rear:	2x USB2.0, 2x USB3.1
Serial Ports:	1 Optional Ports Available
PSU:	180W 100-240VAC 60-50Hz
Lead Time:	5 Working Days
Audio Ports:	3.5mm Ports (Stereo Out, Mic In, Line In)
Warranty:	Standard Only

CASE INFORMATION

Front USB:	1x USB3.0
Hot Swap HDD Bay:	Not available with this case
PCI E Slots:	Not available with this case
Power Supply:	Single 110-230VAC, 12-48VDC or PoE++
Weight:	5 KG
Size:	297x196x58mm

To discuss your requirements or get a bespoke solution for your rack mountable PC needs, please **contact us today**.

+49 (0)6187 290150
sales@g2digital.de